



D40



M	Length
M8	80
M10	50
M10	100
M12	50
M12	100
M12	150

Base: Reinforced Polyamide with Rubber Pad;
Spindle and Nut: Carbon Steel Nickel Plated, or Stainless Steel;
Max Load: 600Kg.


D50



M	Length
M8	80
M10	50
M10	100
M12	50
M12	100
M12	150

Base: Reinforced Polyamide with Rubber Pad;
Spindle and Nut: Carbon Steel Nickel Plated, or Stainless Steel;
Max Load: 1000Kg.


D60



M	Length
M14	100
M14	150
M16	50
M16	100
M16	150
M20	100
M20	150

Base: Reinforced Polyamide with Rubber Pad;
Spindle and Nut: Carbon Steel Nickel Plated, or Stainless Steel;
Max Load: 1000Kg.


D80



M	Length
M14	100
M14	150
M16	50
M16	100
M16	150
M20	100
M20	150
M24	150

Base: Reinforced Polyamide with Rubber Pad;
Spindle and Nut: Carbon Steel Nickel Plated, or Stainless Steel;
Max Load: 1200Kg.

D100



M	Length
M16	50
M16	100
M16	150
M20	100
M20	150
M24	150

Base: Reinforced Polyamide with Rubber Pad;
Spindle and Nut: Carbon Steel Nickel Plated, or Stainless Steel;
Max Load: 1500Kg.